

Material - Nylon (Polyamide 6)				
Diameter (mm)	10	10	10	10
Length (mm)	100	120	140	160
Drilling Diameter (mm)	10	10	10	10
Min. Drilling Depth (mm)	110	130	150	170
Min. Drilling Depth (mm)	110	130	150	170
Min. Installation length (mm)	100	120	140	160
Max. Using Length (mm)	20	35	55	80
Pull out tension value non cracked concrete (kN)	2.50	2.50	2.50	2.50
Pull out tension value cracked concrete (kN)	1.62	1.62	1.62	1.62
Pull out tension value light concrete (kN)	1.50	1.50	1.50	1.50
Pull out tension value areated concrete (kN)	0.70	0.70	0.70	0.70

Product code	Plug Size	Plug length (mm)	Screw thread diameter (mm)	Hole depth through work piece	Fastening Thikness (mm)	Package content
NFP08060SC	M08	60	5	70	10	100
NFP08080SC	M08	80	5	90	30	100
NFP08100SC	M08	100	5	110	50	100
NFP08120SC	M08	120	5	130	70	50
NFP08140SC	M08	140	5	150	90	50
NFP10080SC	M10	80	6	90	30	50
NFP10100SC	M10	100	6	110	50	50
NFP10120SC	M10	120	6	130	70	50
NFP10140SC	M10	140	6	150	90	50
NFP10160SC	M10	160	6	170	110	50

Product code	Plug Size	Plug length (mm)	Screw thread diameter (mm)	Hole depth through work piece(mm)	Fastening Thikness (mm)	Package content
NFP08060SC	M08	60	5	70	10	100
NFP08080SC	M08	80	5	90	30	100
NFP08100SC	M08	100	5	110	50	100
NFP08120SC	M08	120	5	130	70	50
NFP08140SC	M08	140	5	150	90	50
NFP10080SC	M10	80	6	90	30	50
NFP10100SC	M10	100	6	110	50	50
NFP10120SC	M10	120	6	130	70	50
NFP10140SC	M10	140	6	150	90	50
NFP10160SC	M10	160	6	170	110	50